

Cevon Pin Hole Tilt Highlighter

CRI97 11W



R516



SPECIFICATIONS

DIMENSIONS	D84 x H85mm
CUT OUT	70mm
CCT / LUMENS	3000K Warm White / 370lm
CRI	97
BEAM ANGLE	35°
TILT ANGLE	20°
INTENSITY AT 2M	268 lux / 1.3m Beam Width from 2m Height
INTENSITY AT 3M	119 lux / 1.9m Beam Width from 3m Height
IP RATING	IP43
LIFESPAN	55,000 Hours L90(10k) TM-21
WARRANTY	5 Year Warranty
MATERIAL	Aluminum , coated optic glass
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC Rated
DRIVER	Under Insulation Dimmable Driver included, pre-wired
APPLICATION	Interior residential downlighting

370
LUMENS

11
WATTS

AC
240V



UID™ Dimmable Under Insulation Driver Included

COLOUR PARAMETERS

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg
3000K	97.6	93.9	94..9	101.0

AVAILABLE IN

DESCRIPTION	CODE
White, 3000K	R516 W3K
Black, 3000K	R516 B3K