



### SPECIFICATIONS

<b>DIMENSIONS</b>	D80mm x H89mm
<b>CUT OUT</b>	75mm
<b>CCT / LUMENS</b>	3000K Warm White / 922lm
<b>CRI</b>	97
<b>BEAM ANGLE</b>	50°
<b>INTENSITY AT 2M</b>	329 lux / 1.9m Beam Width from 2m Height
<b>INTENSITY AT 3M</b>	146 lux / 2.8m Beam Width from 3m Height
<b>IP RATING</b>	IP43
<b>LIFESPAN</b>	55,000 Hours L90(10k) TM-21
<b>WARRANTY</b>	5 Year Warranty
<b>MATERIAL</b>	Aluminum , coated optic glass
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	Under Insulation Dimmable Driver included, pre-wired
<b>INSTALLATION</b>	Cut holes with extra caution (5mm rim)
<b>APPLICATION</b>	Interior residential downlighting

**922**  
LUMENS

**11**  
WATTS

**AC**  
240V



UID™ Dimmable Under Insulation Driver Included

### COLOUR PARAMETERS

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg
3000K	97.6	93.9	94..9	101.0

### AVAILABLE IN

DESCRIPTION	CODE
White, 3000K	R530 W3K
Black, 3000K	R530 B3K