



### SPECIFICATIONS

<b>DIMENSIONS</b>	D65 x H71mm
<b>CUT OUT</b>	60mm
<b>CCT / LUMENS</b>	3000K Warm White / 676lm with Black Reflector or 685lm with White / Silver Reflector
<b>CRI</b>	97
<b>BEAM ANGLE</b>	60°
<b>INTENSITY AT 2M</b>	211 lux / 2.3m Beam Width from 2m Height
<b>INTENSITY AT 3M</b>	94 lux / 3.5m Beam Width from 3m Height
<b>IP RATING</b>	IP43
<b>LIFESPAN</b>	55,000 Hours L90(10k) TM-21
<b>WARRANTY</b>	5 Year Warranty
<b>MATERIAL</b>	Aluminum, coated optic glass
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	Under Insulation Dimmable Driver included, pre-wired
<b>INSTALLATION</b>	Cut holes with extra caution (5mm rim)
<b>APPLICATION</b>	Interior residential downlighting

<b>&lt;685 LUMENS</b>	<b>11 WATTS</b>	<b>AC 240V</b>
-----------------------	-----------------	----------------

	UID™ Dimmable Under Insulation Driver Included
--	--

### COLOUR PARAMETERS

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg
3000K	97.8	63.3	91.0	101.3

### AVAILABLE IN

DESCRIPTION	CODE
White / White, 3000K	R535 WW3K
White / Black, 3000K	R535 WB3K
Black / Black, 3000K	R535 BB3K
Black / Gold, 3000K	R535 BG3K
White / Gold, 3000K	R535 WG3K
White / Silver, 3000K	R535 WS3K
Black / Silver, 3000K	R535 BS3K