

## Recessed Retrofit Dimmable Downlight IP44 Smart Tilt Classic Series

goLink

R692



### SPECIFICATIONS

<b>DIMENSIONS</b>	D96 x H79mm
<b>CUT OUT</b>	82-84mm
<b>CCT / LUMENS</b>	3000K Warm White / 900lm 4000K Natural White / 950lm 3000-2000K Sunset Dim / 700lm
<b>IP RATING</b>	IP44
<b>CRI</b>	Standard / CRI80 Sunset Dim / CRI90 Sunwave True Spec / CRI97 (Special Order)
<b>LIFESPAN</b>	50,000 Hours (L70)
<b>WARRANTY</b>	5 Year Warranty
<b>BEAM ANGLE</b>	60°
<b>TILT ANGLE</b>	30° (Complete with patented IP44 tilt gasket)
<b>MATERIAL</b>	Aluminum , PC
<b>CLEARANCE</b>	25mm from rear of heatsink to building elements
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	Under Insulation Dimmable Go Link 260mA Driver features power indicator safety light
<b>APPLICATION</b>	Interior only, suitable for new and retrofit applications

**AC**  
240V

**9.5**  
WATTS

**<950**  
LUMENS

### AVAILABLE IN

DESCRIPTION	CODE
White / 3000K / 900lm	R692 W3K
White / 3000K / 900lm / 10 Pack	R692 W3K10
White / 4000K / 950lm	R692 W4K
White / 3K-2K Sunset Dim / 700lm	R692 W32K
Black / 3000K / 900lm	R692 B3K
Black / 3000K / 950lm	R692 B4K
Silver / 3000K / 900lm	R692 S3K
Brushed Chrome / 3000K / 900lm	R692 BC3K



Supplied with Halcyons own quick install go link drivers. Halcyon Go link drivers are designed by Halcyon with extra large terminals and earth loop with easy clamp system for unparalleled installation speed and safety.