



**SPECIFICATIONS**

<b>DIMENSIONS</b>	D86 x H95mm
<b>CUT OUT</b>	72mm
<b>COLOUR TEMP</b>	3000K Warm White
<b>IP RATING</b>	IP44
<b>CRI</b>	80
<b>DIODE / LIFESPAN</b>	Lexar LED / 50,000 Hours
<b>BEAM ANGLE</b>	60°
<b>MATERIAL</b>	Aluminium
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>APPLICATION</b>	Residential / Commercial Interior
<b>DRIVER</b>	Dimmable UID™ Included (Pre-wired) 260mA

**ACCESSORIES**

<b>800 LUMENS</b>	<b>9.5 WATTS</b>	<b>AC 240V</b>
-------------------	------------------	----------------

	UID™ Dimmable Under Insulation Driver Included
---	--



**AVAILABLE IN**

DESCRIPTION	CODE
White in 3000K	R763 KWWUDL
White, Sunset Dim 3000-2000K, CRI95, 650lm	R763 KWCUDL
Brushed Chrome in 3000K	R763 KBCWUDL
Silver in 3000K	R763 KSWUDL
Black in 3000K	R763 KBWUDL



PB13 Recessed Plaster Mouldings set the downlight back into the ceiling space. Once finished the setback creates a perfectly flat ceiling line with “invisible” downlights. Halcyon recessed plaster mouldings create an extra low glare lighting effect for the ultimate lighting ambience and add an extra finishing touch to all high end installations.  
**Pictured: R763 PB13 & R763 KWWUDL Downlight**