



Note: When on, light grazes vertical sides creating a soft ambient effect.

SPECIFICATIONS

| | |
|------------------------|--|
| DIMENSIONS | L115 x W115 x H90mm |
| CUT OUT | L95 x W95mm |
| COLOUR TEMP | 3000K Warm White |
| CRI | 97 |
| BEAM ANGLE | 50° |
| TILT | 0 - 30° |
| ROTATE | 0 - 358° |
| INTENSITY AT 2M | 331 lux / 1.8m Beam Width from 2m Height |
| INTENSITY AT 3M | 147 lux / 2.7m Beam Width from 3m Height |
| IP RATING | IP43 |
| LIFESPAN | 55,000 Hours L90(10k) TM-21 |
| WARRANTY | 5 Year Warranty |
| MATERIAL | Aluminum , coated optic glass |
| CLEARANCE | 25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements. |
| CLASSIFICATION | IC Rated |
| DRIVER | Under Insulation Dimmable Driver included, pre-wired |
| APPLICATION | Interior residential downlighting |

983
LUMENS

11
WATTS

AC
240V



UID™ Dimmable Under Insulation Driver Included

COLOUR PARAMETERS

| CCT | CRI | CRI R9 | TM30 Rf | TM30 Rg |
|-------|------|--------|---------|---------|
| 3000K | 97.1 | 95.6 | 95.0 | 101.6 |

AVAILABLE IN

| DESCRIPTION | CODE |
|--------------|----------|
| White, 3000K | R511 W3K |
| Black, 3000K | R511 B3K |

ACCESSORIES

| DESCRIPTION | CODE |
|---------------|-------------|
| 24° Reflector | R511 REF24D |