

Recessed Downlight Kit LEDE Economy Smart Tilt Select IP44



R773



SPECIFICATIONS

DIMENSIONS	D103 x H63mm
CUT OUT	Ø 92mm
COLOUR TEMP	Selectable 3000K Warm White or 4000K Natural White
LUMENS	White: 3000K Warm White 800lm 4000K Natural White 850lm Black: 3000K Warm White 750lm 4000K Natural White 800lm
CRI	90+
LIFESPAN	52,000 Hours (L90)
BEAM ANGLE	90°
TILT ANGLE	25° (Patented IP44 tilt gasket)
MATERIAL	Aluminium, PC
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F Rated
DRIVER	Included (Pre-wired) Under Insulation Dimmable 260mA
APPLICATION	Residential / Commercial Interior
WARRANTY	5 Year Warranty

12 WATTS	<850 LUMENS	AC 240V
--------------------	--------------------------	-------------------

	UID™ Dimmable Under Insulation Driver Included
--	--

select CCT

AVAILABLE IN

DESCRIPTION	CODE
Black 3000K/4000K Tilt "Select" Dual Colour, Dimmable	R773 B34
White 3000K/4000K Tilt "Select" Dual Colour, Dimmable	R773 W34