

R772

LEDE

## Recessed Fixed Downlight Kit LEDE Economy Select



### SPECIFICATIONS

<b>DIMENSIONS</b>	D120 x H53mm
<b>CUT OUT</b>	Ø 100 - 110mm
<b>COLOUR TEMP</b>	Selectable 3000K Warm White or 4000K Natural White
<b>LUMENS</b>	<b>White:</b> 3000K Warm White 1100lm 4000K Natural White 1150lm <b>Black:</b> 3000K Warm White 1050lm 4000K Natural White 1100lm
<b>CRI</b>	90+
<b>LIFESPAN</b>	52,000 Hours (L90)
<b>BEAM ANGLE</b>	90°
<b>MATERIAL</b>	Aluminium, PC
<b>IP RATING</b>	IP44
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC-F Rated
<b>DRIVER</b>	Included (Pre-wired) Under Insulation Dimmable 350mA
<b>APPLICATION</b>	Residential / Commercial Interior
<b>WARRANTY</b>	5 Year Warranty

<1150  
LUMENS

15  
WATTS

AC  
240V



UID™ Dimmable Under  
Insulation Driver Included

select CCT

### AVAILABLE IN

DESCRIPTION	CODE
Black 3000K/4000K "Select" Dual Colour, Dimmable	R772 B34
White 3000K/4000K "Select" Dual Colour, Dimmable	R772 W34