



**SPECIFICATIONS**

<b>DIMENSIONS</b>	D102 x H96mm
<b>CUT OUT</b>	Ø 92mm
<b>COLOUR TEMP</b>	3000K Warm White
<b>LUMENS</b>	White Reflector 720lm or Black Reflector 630lm
<b>CRI</b>	90
<b>LIFESPAN</b>	50,000 Hours
<b>BEAM ANGLE</b>	60°
<b>TILT ANGLE</b>	30° (Patented IP44 tilt gasket)
<b>MATERIAL</b>	Aluminum and Patented PC Heat Shield
<b>IP RATING</b>	IP44
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 260mA
<b>APPLICATION</b>	Residential / Commercial Interior
<b>WARRANTY</b>	5 Year warranty

<b>&lt;720 LUMENS</b>	<b>12 WATTS</b>	<b>AC 240V</b>
---------------------------	---------------------	--------------------

	UID™ Dimmable Under Insulation Driver Included
---	---

**AVAILABLE IN**

DESCRIPTION	CODE
White with White Reflector 3000K	R757 WW3UK
White with Black Reflector 3000K	R757 WB3UK
Black with Black Reflector 3000K	R757 BB3UK
Silver with White Reflector 3000K (CRI80, 850lm)	R757 SW3UK
Silver with Black Reflector 3000K	R757 SB3UK

Superseded by R750