


SPECIFICATIONS

DIMENSIONS	D86 x H66mm
CUT OUT	Ø 80mm
COLOUR TEMP	3000K Warm White
CRI	97+
LIFESPAN	55,000 Hours L90(10k) TM-21
BEAM ANGLE	40°
TILT	25° Tilt
ROTATE	355° Rotate
MATERIAL	Aluminum
IP RATING	IP20
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC Rated
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 260mA
INSTALLATION	Cut holes with extra caution (6mm rim)
APPLICATION	Interior residential downlighting
WARRANTY	5 Year Warranty

740
 LUMENS

11
 WATTS

AC
 240V

 UID™ Dimmable Under
 Insulation Driver Included

AVAILABLE IN

DESCRIPTION	CODE
White / White 3000K	R544 WW3K
White / High Gloss Black 3000K	R544 WB3K
White / Matte Black 3000K	R544 WMB3K
White / Gold 3000K	R544 WG3K
White / Silver 3000K	R544 WS3K
Black / High Gloss Black 3000K	R544 BB3K
Black / Matte Black 3000K	R544 BMB3K
Black / Gold 3000K	R544 BG3K
Black / Silver 3000K	R544 BS3K