



### SPECIFICATIONS

<b>DIMENSIONS</b>	D86 x H95mm
<b>CUT OUT</b>	Ø 72mm
<b>COLOUR TEMP</b>	3000K Warm White
<b>CRI</b>	90
<b>LIFESPAN</b>	50,000 Hours
<b>BEAM ANGLE</b>	60°
<b>MATERIAL</b>	Aluminium
<b>IP RATING</b>	IP44
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>APPLICATION</b>	Residential / Commercial Interior
<b>DRIVER</b>	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 260mA
<b>WARRANTY</b>	5 Year Warranty

<b>720 LUMENS</b>	<b>9.5 WATTS</b>	<b>AC 240V</b>
-------------------	------------------	----------------

	UID™ Dimmable Under Insulation Driver Included
---	--



### AVAILABLE IN

DESCRIPTION	CODE
White 3000K	R763 KWWUDL
White Sunset Dim 3000-2000K, CRI95, 550lm	R763 KWCUDL
Brushed Chrome 3000K	R763 KBCWUDL
Silver 3000K	R763 KSWUDL
Black 3000K	R763 KBWUDL

### ACCESSORIES

DESCRIPTION	CODE
R763 Mini Downlight Recessed Trimless Plaster Mould 72mm C/O 86mm O/D	R763 PB13



PB13 Recessed Plaster Mouldings set the downlight back into the ceiling space. Once finished the setback creates a perfectly flat ceiling line with "invisible" downlights. Halcyon recessed plaster mouldings create an extra low glare lighting effect for the ultimate lighting ambience and add an extra finishing touch to all high end installations.  
**Pictured: R763 PB13 & R763 KWWUDL Downlight**