

R763K MINI FIXED

LED QUICK CONNECT FIXED KIT C/W DIMMABLE DRIVER



Watts	Lumens	mA	CRI	Cut Out	Classification
9.5W	800	260	80	72mm	IC

Diode: Lextar 60° Constant Current (<40,000hrs) **IP44**
 Material: Aluminium
 Dimensions: D86 x H95mm
 Driver: Included
 Available in: R763 KSWDL (Silver in 3000K WW)
 R763 KWWDL (White in 3000K WW)
 R763 KBCWDL (Brushed Chrome in 3000K WW)



DRDACC260 I2W Dimmable

R737K SMART TILT

LED QUICK CONNECT 25° AIRTIGHT TILT KIT C/W DIMMABLE DRIVER



Watts	Lumens	mA	CRI	Cut Out	Classification
9.5W	800	260	80	82mm	IC

Diode: Lextar 60° Constant Current (<40,000hrs) **IP44**
 Material: Aluminium
 Dimensions: D105 X H80mm
 Driver: Included
 Available in: R737 KSWDL (Silver in 3000K WW)
 R737 KWWDL (White in 3000K WW)
 R737 KBCWDL (Brushed Chrome in 3000K WW)
 R737 KCWDL (Chrome in 3000K WW)
 R737 KPWWDL (Prismatic Lens, White in 3000K WW)
 R737 KPWWDL (Prismatic Lens IO Pack, White in 3000K WW)



DRDACC260 I0W Dimmable

RETROFIT

82mm