

R772

LEDE

Recessed Fixed Downlight Kit LEDE Economy Select



SPECIFICATIONS

DIMENSIONS	D120 x H53mm
CUT OUT	Ø 100 - 110mm
COLOUR TEMP	Selectable 3000K Warm White or 4000K Natural White
LUMENS	White: 3000K Warm White 1100lm 4000K Natural White 1150lm Black: 3000K Warm White 1050lm 4000K Natural White 1100lm
CRI	90+
LIFESPAN	52,000 Hours (L90)
BEAM ANGLE	90°
MATERIAL	Aluminium, PC
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F Rated
DRIVER	Included (Pre-wired) Under Insulation Dimmable 350mA
APPLICATION	Residential / Commercial Interior
WARRANTY	5 Year Warranty

<1150
LUMENS

15
WATTS

AC
240V



UID™ Dimmable Under
Insulation Driver Included

select CCT

AVAILABLE IN

DESCRIPTION	CODE
Black 3000K/4000K "Select" Dual Colour, Dimmable	R772 B34
White 3000K/4000K "Select" Dual Colour, Dimmable	R772 W34